


KING^{US}
Solution Corp.

Low Pressure Molding
An innovative process:
20~500psi(1.5~30Kgf/cm²)
To replace the epoxy potting
for protection of fragile
electronic components.



C Type Shuttle Table  
Low Pressure Molding Machine

C Type Low Pressure Molding Machine



- Machine driven by pneumatics and servo motor, energy saving, low pollution and no oil leakage, suitable for clean room and laboratory.
- The Pressure adjusting valve control the pressure of injection.
- TWO PID thermal temperature control zones(Melting tank and nozzle).
- Melt tank made from aluminum alloy, Teflon coated, heating evenly and rapidly, much easier to clean.
- Nozzle connected to melt tank, injection unit driven by air pressure.
- Nozzle directly connected to gear pump and no heating pipe, avoid material crystallization.
- Tie-barless (Ctype)design gives more space for operation. Especially suitable for the power cord and connector with wire.
- Sealing cover, Safety Light curtain, pneumatic door and dual palm safety button for personnel safeguard.
- Multi-Language PC Base industrial type Linux core system.
- 1000 sets of mold settings can be stored and export as backup.
- Complete record of history settings & warnings. Built in USB connect.
- On-line operation and maintenance service.

Model		KL-CX-01-2-09-1
INJECTION UNIT		
Injection Type		Horizontal injection from parting line
Capacity	L	3.5 / 6.5 *Optional
Injection Capacity	ml/r	8.98
Pump Speed	r.p.m.	0~100
Nozzle Stroke	mm	50
Nozzle Contact Force	Tf	0.06
CLAMPING UNIT		
Clamping System		Pneumatic Air Booster
Clamping Force	Tf	1 4
Opening Stroke	mm	160
Mould Space	mm	285
Min Mould Space	mm	125
Overall Size of Platens	mm	400*150
Space Between Columns	mm	N/A
Size Of Shuttler Platen	mm	850*160 *Optional
Shuttle Plate Stroke	mm	500 *Optional
Ejector		Pneumatic
Ejector Force	Tf	0.12
Ejector Stroke	mm	(UP) 25
ELECTRICAL EQUIPMENT & GENERAL		
Power Source / Voltage	V/HZ	1Φ-220v (60Hz / 50Hz)
Drive Motor	KW	0.4
Heater	KW	4.8
Temperature Control Zone	ZONE	3
Hydraulic System Pressure	kgf/cm²	6
Machine Dimension	m	1.65*1.00*1.75
Machine Weight	ton	0.8

KING'S Solution Corp.

Taiwan : No.457, Nanshang Rd., Guishan Dist, Taoyuan City 33392, Taiwan | sales@kingsmachinery.com.tw | Tel: +886-3-3218768 | Fax: +886-3-3218769
China : Bao Xin Industrial Park, Wu Village, Chen Jiang Town, Hui Zhou City, Guangdong, China | Tel: +86-752-3269005/07 | Fax: +86-752-3269360/350
www.injection.com.tw/ | www.facebook.com/Kingsmachinery/ | <https://www.youtube.com/user/kingsmachinery/>

