



Plastic Wood Composite Profile Extruding Machine

規格 SPECIFICATIONS


型號	MODEL NO.	CY-50PW	CY-65PW	CY-70PW	CY-80PW	CY-100PW
押出量	EXTRUDING CAPACITY (KGS/HR)	20~40	30~55	35~65	50~80	70~100
螺旋桿直徑	SCREW DIAMETER (MM)	50m/m	65m/m	70m/m	80m/m	100m/m
螺旋桿直徑比	SCREW L/D RATIO	25:1	25:1	25:1	25:1	25:1
傳動馬力	DRIVING MOTOR	15HP VF	20HP VF	25HP VF	40HP VF	50HP VF
電熱容量	HEATER CAPACITY (KW)	6KW	8KW	12KW	16KW	22KW
溫度控制	TEMPERATURE CONTROL (POINTS)	5	6	6	7	8
冷卻設備	COOLING EQUIPMENT	5HP	5HP	7.5HP	7.5HP	10HP
引取機	TAKE-OFF UNIT	履帶式 CATERPILLA				
傳動馬力	DRIVING MOTOR	2HP VF	3HP VF	3HP VF	5HP VF	5HP VF
切斷機	CUTTING DEVICE	風壓控制 AIR CONTROL				
傳動馬力	DRIVING MOTOR	2HP	2HP	2HP	2HP	2HP
重量	WEIGHT	3800 KGS	4200 KGS	4500 KGS	5300 KGS	6500 KGS
佔地尺寸	USED FLOOR SPACE L×W×H	12M×0.9M×1.8M	16M×0.9M×1.8M	17M×1.5M×1.8M	18M×1.6M×1.8M	20M×1.8M×1.9M

※本表僅供參考，本公司保留修改權


振宇塑膠機械有限公司
CHEN YU PLASTIC MACHINE

公司：台灣嘉義市福州八街17號
NO.17, FU CHOU 8 ST., CHIA YI CITY, TAIWAN
Tel: 886-5-284-2689 Fax: 886-5-284-4189
E-mail: cy0533@ms25.hinet.net <http://www.chenyu-web.com>

Plastic Wood Composite Profile Extruding Machine



Can Be Stick



Can Be Plain



Can Be Cut By a Saw



Can Be Nailed



Fire-Retardant



Water-Resistant

Professional PVC Machinery Manufacturer Planning & Whole-Plant Deliver

1. PVC Profile Extrusion
2. PVC Plastic Pellet M/C
3. PVC Rigid & Soft Pipes M/C
4. Waste Plastic Recycling M/C
5. Plastic Wood Composite Profile
Extruding Machine



New Revolution Wood Composite Material

Attributes of Wood Composite:

- Recyclable
- Fire Retardant
- Water Resistant
- Insect Resistant
- Maintenance Free
- High Impact Strength
- No Finishing Required
- Resistance to Weathering
- Free From Natural Defects
- Close Resemblance to Natural Wood

Applications:

- Flooring
- Skirtings
- Wall panels
- Picture frames
- Curtain pole set
- Door and window frames

