



SINCE 1979

HEMINGSTONE

THE FIRST CHOICE

峰明机械有限公司**HEMINGSTONE MACHINERY CO., LTD.**

No. 41, Wu-Kong 5 Rd., Wu-Ku Industrial Park,
Wu-Ku Dist., New Taipei City 248, Taiwan
Tel: +886-2-2299-1616, 2299-5700
Fax: +886-2-2299-2070, 2299-2080
E-mail: hm.stone@msa.hinet.net
hm_mail@hemingstone.com
www.hemingstone.com

2 Lines Bottom Sealing Machine for Bags On Rolls with Core for Star Sealing Bag, Vegetable Bag and Bottom Sealing with Side Gusset Bag (Without Folding Unit, Edge Guider and Side Gusset Unit)

**HM-800CB**

Features

- High speed bottom sealing machine with perforation and paper core rewind. Maximum speed up to 100m/min.
- Fixed distance between sealing and perforation, no adjustments required.
- Fully automatic paper core changing system
- A, B lines are separately controlled to minimize wastage
- Tension control by air; no tension at the sealing point therefore enhances sealing strength and quality.
- HD, LD, LLD and recycled materials applicable.
- Can produce vegetable bag, star sealing bag and gusseted bottom sealing bag.

- Maquina de alta velocidad de sello de fondo con perforación y rebobinador con cono de papel. Máxima velocidad hasta 100m/min.
- Distancia fija entre sellado y perforación, no requiere ajustes.
- Sistema de cambio automático del cono.
- Líneas A, B son controladas separadamente para minimizar desperdicios.
- Control de tensión por aire; sin tensión en el punto de sellado para fortalecer la calidad y fuerza de sellado.
- Compatible con material HD, LD, LLD y reciclado.
- Produce bolsa para vegetal, bolsa sellado estrella y bolsa sello fondo con fuelles.

- ماكينة اللحام السفلى عالية السرعة مع سكين التخريم ووحدة اللف للكور الورقية.
السرعة القصوى تصل الى 100 متر / للدقيقة.

- المسافة بين خط اللحام و سكين التخريم مثبته , ولا تحتاج الى ضبط.

- نظام تغيير الكور الورقية اوتوماتيكي بالكامل .

- التحكم المنفصل و الذاتي لكل خط و ذلك لتقليل التلف.

- التحكم في الجهد بالهواء , حيث لا يوجد جهد عند نقطة اللحام و ذلك لتعزيز قوة و جودة اللحام.

- كافة الخامات , HD, LD, LLD و المواد المعاد تدويرها قابلة للاستخدام .

- تخصص الماكينة لانتاج كيس الخضروات , لحام شكل النجمة , اكياس لحام سفلى مع عصفه جانبية

With Core



	Bag Size		Thickness for vegetable bag & bottom sealing with gusset bag (min.-max.) mm	Thickness for star sealing bag (min.-max.) mm	Speed (pcs/min)	Line Speed (m/min)	Speed for Changing the Roll (times/max.)	Production of Rolls		Power Required (kw)	Machine Dimensions			Air Compressor (not included) (hp)
	Width (mm)	Length (mm)						Roll Width (mm)	Roll dia. (mm/max.)		L (m)	W (m)	H (m)	
HM-800CB	150-300 x 2 lines	150-1000	0.02-0.15	0.02-0.12	50-230	100	5	150-300 x 2 lines	180	7	7.6	2.17	2	5