

AFM

阿莎麗夾鏈線

asar
PLASTIC CORPORATION



上旋轉多層膜高速吹袋押出機

AFM-45/55/65

**MULTI-LAYER OSCILLATING
HIGH SPEED FILM BLOWN
MACHINE**



規格表 SPECIFICATIONS

MODEL 型號	AFM-45	AFM-55	AFM-65
Production 產品	LDPE+LLDPE+LDPE;LLDPE+HDPE+LLDPE;LLDPE+EVA+LDPE		
Thickness of film 厚度	LDPE:0.012-0.25mm		
Width of film (max) 最大寬度	650 m/m	1100 m/m	1350 m/m
Max. Output 最大產量	60-80 kgs/hr	110-120 kgs/hr	160-170 kgs/hr
EXTRUDER A. 押出機	LOW BASE TYPE		
Screw Dia. 螺桿直徑	45 m/m	55 m/m	65 m/m
L/D Ratio 長徑比	30:1	30:1	30:1
Screw & Barrel Material 螺桿與砲筒質料	SCM-2 with Polished & Nitrided Treatment 經氮化處理		
Heat Zones of Barrel 砲筒溫度控制	2 points	2 points	3 points
Barrel Heat Capacity 砲筒電熱	8 kw	11.2 kw	14.4 kw
Main Driving Motor 主馬達	20 HP + Inverter	40 HP + Inverter	50 HP + Inverter
Barrel Cooling 砲筒冷卻風車	1/4 HP x 1 set	1/4 HP x 2 sets	1/4 HP x 3 sets
EXTRUDER B. 押出機	LOW BASE TYPE		
Screw Dia. 螺桿直徑	45 m/m	55 m/m	65 m/m
L/D Ratio 長徑比	30:1	30:1	30:1
Screw & Barrel Material 螺桿與砲筒質料	SCM-2 with Polished & Nitrided Treatment 經氮化處理		
Heat Zones of Barrel 砲筒溫度控制	2 points	2 points	3 points
Barrel Heat Capacity 砲筒電熱	8 kw	11.2 kw	14.4 kw
Main Driving Motor 主馬達	20 HP + Inverter	40 HP + Inverter	50 HP + Inverter
Barrel Cooling 砲筒冷卻風車	1/4 HP x 1 set	1/4 HP x 2 sets	1/4 HP x 3 sets
EXTRUDER C. 押出機	LOW BASE TYPE		
Screw Dia. 螺桿直徑	45 m/m	55 m/m	65 m/m
L/D Ratio 長徑比	30:1	30:1	30:1
Screw & Barrel Material 螺桿與砲筒質料	SCM-2 with Polished & Nitrided Treatment 經氮化處理		
Heat Zones of Barrel 砲筒溫度控制	2 points	2 points	3 points
Barrel Heat Capacity 砲筒電熱	8 kw	11.2 kw	14.4 kw
Main Driving Motor 主馬達	20 HP + Inverter	40 HP + Inverter	50 HP + Inverter
Barrel Cooling 砲筒冷卻風車	1/4 HP x 1 set	1/4 HP x 2 sets	1/4 HP x 3 sets
THREE LAYER DIE 三層模頭			
Type 型式	Inflation Spiral Type 向上螺旋型		
Die-Lip Dia 模頭直徑	LDPE 200 m/m	LDPE 250 m/m	LDPE 350 m/m
Die Heat Zones 模頭溫度控制	2 points	2 points	2 points
Die Heat 模頭電熱	20 kw	25.4 kw	30 kw
Adaptor Heating (1 point) 模頭接頭電熱	1.6 kw x 2 sets	1.8 kw x 2 sets	2.2 kw x 2 sets
Air Ring 風環	1 set	1 set	1 set
Blower 送風機	5 HP	5 HP	5 HP
TAKE-UP UNIT (ROTARY TYPE) 引取台(旋轉式)			
Screw Dia. 引取輪寬	1000 m/m	1200 m/m	1500 m/m
L/D Ratio 引取馬達	1 HP DC (1/10)	1 HP DC (1/10)	2 HP DC (1/10)
WINDER 捲取台			
Type 型式	Two Stations Surface Winder 雙邊捲取台		
Winding Speed 捲取速度	0-100 M/min		
Winding Torque 捲取轉距馬達	0.3 Kgm	0.3 Kgm	0.4 Kgm
Winding Roller 捲取輪	250 x 1000 m/m	250 x 1200 m/m	250 x 1500 m/m