

Super High Speed Plastic Inflation Machine
HDPE / LDPE / LLDPE
(A/B/A) TWO LAYER
雙層(A/B/A)高速吹袋機

KMTL

KMTL-50S



KANG CHYAU



Whole Plant for Plastic Bags Making Machine

Specification

MODEL 機型	KMTL-50S
SUITABLE MATERIAL 適用原料	HDPE / LDPE / LLDPE
FILM THICKNESS 膜厚	0.010~0.15 mm
FILM WIDTH RANGE 膜寬	1200 mm
FILM OUTPUT 最大膠膜產量	90~140 kgs / hr
EXTRUDER UNIT 主機部份	
SCREW DIAMETER / TYPE 螺桿直徑 / 型號	Ø 50 mm x 2
SCREW L / D RATIO 螺桿長徑比	30 : 1
HEATING CAPACITY 電熱量	25.8 kw
AUTO THERMO CONTROL 溫控點	8 zone
BARREL COOLING FAN 螺桿冷卻風扇	1/8 hp x 6
DRIVING MOTOR 主驅動馬達	AC 30 hp + INVERTER
DIE UNIT 模頭部份	
DIE DIAMETER 模頭直徑	H: 100 / 150 mm (A/B/A)
AIR RING DIAMETER 風環直徑	H: φ 165 mm
HEATING CAPACITY 電熱量	14 kw
AUTO THERMO CONTROL 溫控點	3 zone
COOLING BLOWER 冷卻風車	7.5 hp
TAKE-UP UNIT 引取部份	
TAKE-UP ROLLER 引取輪寬	1300 mm
EFFECTIVE WIDTH 有效引取輪寬	1200 mm
TAKE-UP MOTOR 引取馬達	SERVO 1.5 kw
TAKE-UP SPEED 引取速度	100 m / min
WINDING UNIT 捲取部份	
ROLLER WIDTH 捲取輪寬	1300 mm
WINDING WIDTH 有效捲取寬度	1200 mm
WINDING MOTOR 捲取馬達	SERVO 1 kw
EQUIPMENT 配備	
ROTATING DIE 旋轉器	

REMARK : The above machine specification and production range can be changed without any notice due to kind of different application.

型錄上之圖片及係數只備參考其尺寸・規格・樣式會因客人所訂購的配件不同而有所改變

康喬工業有限公司

KANG CHYAU INDUSTRY CO., LTD.

247 新北市蘆洲區復興路 227 巷 28 弄 2-10 號

No. 2-10, Aly. 28, Ln. 227, Fuxing Rd., Luzhou Dist., New Taipei City 247, Taiwan

Mail Box: P. O. Box 5-56, Luzhou Dist., New Taipei City 247, Taiwan

Tel: +886-2-22856880-1 Fax: +886-2-22856883

E-mail: kang.chyau@msa.hinet.net Internet: www.kangchyau.com.tw

