

▶ KSF-0610DB-3L



Specification			KSF-0610DB-3L
成品容積	Product Volume	liter	10 L ~ 30 L
螺桿直徑	Screw Diameter	mm	60 mm + 60 mm + 90 mm
模板尺寸	Platen Size	-	600 mm x 1000 mm
鎖模力	Clamping Force	-	45 ton
押出機馬達	Extruder Motor	HP	40 HP + 40 HP + 75 HP
押出機速率	Extrusion Speed	kg / hr	340 (MAX)
控制系統	Control System	-	電腦化色彩觸控操作 Computerised with Color Touch Screen
厚薄控制	Parision Control	-	100 Points
模頭	Die Head	-	雙模頭/連續式 Double Head/Continuous
加熱片	Heating Band	-	不鏽鋼 Stainless Steel, 53 kw
加熱區	Heating Zone	-	6
切刀方式	Cutting	-	冷切 Cold Cutter
開隙	Daylight	-	335 mm ~ 815 mm
夾模台移動	Clamp Movement	-	7 kw 伺服馬達控制 Servo Motor
押出機升降	Platform Movement	-	5 HP 減速機馬達 Electric Motor
油壓幫浦馬達	Hydraulic Pump Motor	-	30HP (節能設計 Energy Saving)

★ 本目錄中所有規格皆有變動，恕不另行通知
Figures and data in this catalogue are subject to change without prior notice due to constant research and development.