

DRY / WET LAMINATING MACHINE



WDWL-H Series



World Leadership



COMPANY PROFILE

Worldly Industrial Co., Ltd. was established in 1997. We sale our products to all over the world with the brand name Worldly. By trading with many international companies, we acquire lots of precious experiences, and applying those experiences to develop innovative design, manufacturing technique, quality management, marketing strategy, and environmental protection. At a long-year operation, our teams accumulate abundant and advanced manufacturing technique in flexible package printing machineries. In addition we innovate and research continuously and integrate those resources with our machineries to provide better service and products for customers around the world.

Worldly Industrial Co., Ltd. locate in Taichung Industry Park where is in the centre of Taiwan. Due to the attitude of insisting on high quality and taking responsibility for our customers, we develop and expand our manufacturing equipment continuously. Now we have achieved high production capacity & quality. All staff in Worldly contribute their abilities and devote themselves to satisfy with customers. We even encourage with our customers to establish good relationship and mutual benefit.



Doctor Blade Device

Doctor blade holder mechanism has double axles with four liners for bearing to fix it. It has the advantages of strong construction and outstanding sensitivity. In addition flexible doctor blade is adjustable for up/down, forward/rearward, and blade angle can adjust slightly to assure the pressure of down moving. Thus, it can have longer service life of gravure cylinder and prevents surface scratching.



Dry-laminating Unit

- 1) Dry laminator circulate by thermo oil inside laminating steel roller to ensure even temperature, solid laminating and create high productivity.
- 2) Protection cover design for prevent nip accident.



Unwind Unit

- 1) Twin-reel rotating non-stop type rewinder (optional disc type).
- 2) Drive motor control by AC vector driver.
- 3) Automatic non-stop splicing. Precise splice device achieves low wastage and keep efficiency procreation.
- 4) E.P.C controller
Edge position control with photo sensor detector and servo motor.



Wet-unwind Unit

Single reel un-winder use magnetic brake unit , and auto tension control.

Wet-coating & Laminating Unit

- 1) 3 rolls type coating unit.
- 2) Pneumatic nip roll for wet lamination.
- 3) Dispenser (smooth) roll for diffusion glue, non-air bubbles appear.



Rewind Unit

- 1) Twin-reel rotating non-stop type rewinder (optional disc type).
- 2) Drive motor control by AC vector driver.
- 3) Automatic non-stop splicing. Precise splice device achieves low wastage and keep efficiency procreation.
- 4) Lay-on roller device with pneumatic pressure and regulator for control on the rewind reel enable keep rewinding the material smooth without sliding.



Integrated Control Panel

Integrated control panel including human-machine interface touch screen, PLC centralized control system, all machine function and parameter can monitoring and control on user friendly production management.



Drying Chamber

All rolls inside dryer tunnel are synchronized driven with power transmission belt.

DRY/WET LAMINATING MACHINE



WDWL-H Series

New model of Laminating Machine Worldly multi-function and high efficient dry & wet laminating machine can apply to working on various materials. Especially the design of two-in-one function has outstanding performance; moreover it can economize your investment cost. Worldly multi-function laminating machine will increase your production and create infinite advantages for future benefit.

Worldly

Specifications

MODEL	WDWL-H
Maximum Machine Speed	220 m/min
Laminating Speed (Must depend on coating relevant condition, such as material and coating thickness)	200 m/min
Laminating Width	800 / 1,000 / 1,200 mm
Maximum Material Diameter	ø 600 mm / ø 800 mm / ø 1,000 mm

** All specifications and drawing are for reference.
The model depend on actual product.*

Application

PET, CPP, PVC, OPP, PP, PE, Nylon, Aluminum Foil, Paper

Features and Construction

- * Combine dry and wet laminating in one machine.
- * Solvent & Water based are available.
- * Laminating width can be used on different materials.
- * High performance synchronized control system by PLC, provides convenient operation.
- * Reversible smoothing roller prevents air bubbles during lamination.
- * Drying system options: thermal oil, gas burner and electric heating.
- * 4-zone drying: high drying performance and non-volatility remain.

Worldly



PRINCIPLE OF MANAGEMENT

Teamwork

Take customers priority

Reputation first

Sustainable business

瑋禮 企業股份有限公司

WORLDLY INDUSTRIAL CO., LTD.

台中市台中工業區7路2號

No.2, 7th Road, Taichung Industrial Park, Taichung City, Taiwan 407

Tel: +886-4-2359 9850 · 2359 9851 Fax: +886-4-2359 6625 · 2358 4485

E-mail: welead@ms17.hinet.net / <http://www.welead.com>



ISO 9001:2008

